

WHIRLING PSYCHROMETER

Determination of relative Air Humidity

The knack of ...

mobile and indirect humidity measurement has the handy instrument. The radiation protected casing contains two liquid thermometers. Dry and humid temperature are measured, then manual aspiration is achieved by whirling the instrument. The graphical psychrometer-table makes the easy determination of relative humidity possible (additional tables on request).

- small, light, handy
- easy handling
- inexpensive and always ready for use
- life-long guarantee* on thermometer function

expeditions • navigation • building services • industrial safety and health standards

*except glass breakage



Professional Line

(740) Whirling Psychrometer

Id-No. 00.07400.000 010

Measuring element:

liquid expansion thermometer

Measuring-/ Application range:

-10...+60°C

Accuracy:

± 0.2°C within the total range • ± 0.1°C within any scale section of 10°C

Resolution/ Scale:

≤ 0.2°C/ 0.2°C

Housing/ Dimensions:

RAL 9010 (clean-white) • 305 x 60 x 22 mm with folded handle

Weight:

0.6 kg

Included in delivery:

psychrometric table (771 b) • 1 moistening tube • 0.5 m of spare wick

Options:

thermometers available in -30...+40°C • thermometers available with official calibration certificate (on request)

Accessories:

[see page 45](#)

